

Continuous heat-shrink conduit



Product information


Labels cannot be applied to the heat-shrink tube. It is designed to:

- protect from moisture
- protect against contamination

Its shrinking takes place by applying heat.

Available in various colors and sizes in dispenser boxes.

Information, conformities and approvals



Article	Order No.	Color	Cable diameter max. mm	Shrinkage area from - to Ø mm	PU pcs.
Continuous roll ware; 15 m roll					
HSD-T2 Box 1,6/0,8 - 15m	88861100	Red	1.6	1.6 - 0.8	1
HSD-T2 Box 1,6/0,8 - 15m	88861200	Blue	1.6	1.6 - 0.8	1
HSD-T2 Box 1,6/0,8 - 15m	88861300	Green / Yellow	1.6	1.6 - 0.8	1
HSD-T2 Box 1,6/0,8 - 15m	88861000	Black	1.6	1.6 - 0.8	1
HSD-T2 Box 2,4/1,2 - 15m	88861101	Red	2.4	2.4 - 1.2	1
HSD-T2 Box 2,4/1,2 - 15m	88861201	Blue	2.4	2.4 - 1.2	1
HSD-T2 Box 2,4/1,2 - 15m	88861301	Green / Yellow	2.4	2.4 - 1.2	1
HSD-T2 Box 2,4/1,2 - 15m	88861001	Black	2.4	2.4 - 1.2	1
Continuous roll ware; 10 m roll					
HSD-T2 Box 3,2/1,6 - 10m	88861102	Red	3.2	3.2 - 1.6	1
HSD-T2 Box 3,2/1,6 - 10m	88861202	Blue	3.2	3.2 - 1.6	1
HSD-T2 Box 3,2/1,6 - 10m	88861302	Green / Yellow	3.2	3.2 - 1.6	1



Continuous heat-shrink conduit

Article	Order No.	Color	Cable diameter max. mm	Shrinkage area from - to Ø mm	PU pcs.
HSD-T2 Box 3,2/1,6 - 10m	88861002	Black	3.2	3.2 - 1.6	1
HSD-T2 Box 4,8/2,4 - 10m	88861103	Red	4.8	4.8 - 2.4	1
HSD-T2 Box 4,8/2,4 - 10m	88861203	Blue	4.8	4.8 - 2.4	1
HSD-T2 Box 4,8/2,4 - 10m	88861303	Green / Yellow	4.8	4.8 - 2.4	1
HSD-T2 Box 4,8/2,4 - 10m	88861003	Black	4.8	4.8 - 2.4	1
HSD-T2 Box 6,4/3,2 - 10m	88861104	Red	6.4	6.4 - 3.2	1
HSD-T2 Box 6,4/3,2 - 10m	88861204	Blue	6.4	6.4 - 3.2	1
HSD-T2 Box 6,4/3,2 - 10m	88861304	Green / Yellow	6.4	6.4 - 3.2	1
HSD-T2 Box 6,4/3,2 - 10m	88861004	Black	6.4	6.4 - 3.2	1
HSD-T2 Box 9,5/4,8 - 10m	88861105	Red	9.5	9.5 - 4.8	1
HSD-T2 Box 9,5/4,8 - 10m	88861205	Blue	9.5	9.5 - 4.8	1
HSD-T2 Box 9,5/4,8 - 10m	88861305	Green / Yellow	9.5	9.5 - 4.8	1
HSD-T2 Box 9,5/4,8 - 10m	88861005	Black	9.5	9.5 - 4.8	1
HSD-T2 Box 12,7/6,4 - 10m	88861106	Red	12.7	12.7 - 6.4	1
HSD-T2 Box 12,7/6,4 - 10m	88861206	Blue	12.7	12.7 - 6.4	1
HSD-T2 Box 12,7/6,4 - 10m	88861006	Black	12.7	12.7 - 6.4	1
Continuous roll ware; 5 m roll					
HSD-T2 Box 19,1/9,5 - 5m	88861107	Red	19.1	19.1 - 9.5	1
HSD-T2 Box 19,1/9,5 - 5m	88861207	Blue	19.1	19.1 - 9.5	1
HSD-T2 Box 19,1/9,5 - 5m	88861307	Green / Yellow	19.1	19.1 - 9.5	1
HSD-T2 Box 19,1/9,5 - 5m	88861007	Black	19.1	19.1 - 9.5	1
Continuous roll ware; 3 m roll					
HSD-T2 Box 25,4/12,7 - 3m	88861108	Red	25.4	25.4 - 12.7	1
HSD-T2 Box 25,4/12,7 - 3m	88861208	Blue	25.4	25.4 - 12.7	1
HSD-T2 Box 25,4/12,7 - 3m	88861308	Green / Yellow	25.4	25.4 - 12.7	1



Continuous heat-shrink conduit

Article	Order No.	Color	Cable diameter max. mm	Shrinkage area from - to Ø mm	PU pcs.
HSD-T2 Box 25,4/12,7 - 3m	88861008	Black	25.4	25,4 - 12,7	1

Material properties



Polyolefin

Thermal properties



Temperature / temperature range

-55 °C - 135 °C

Fire properties



Fire classification

Highly flame retardant in accordance with UL 224 - VW-1

Technical information



UV-resistant acc. to ISO 4892-2

Conformity



RoHS (EC Directive 2011/65/EU)

Classification

ETIM 9: EC002254
ECLASS 14: 27400105
UNSPSC 26.0801: 39121723

General technical data



Assembly method

0000000000001

Assembly method



Heat-shrink tube system

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.