



Type EW-PA



Product information

The EW-PA cable protection conduits are made of specially modified polyamide 6. The material is halogen, phosphor and cadmium-free. The conduits are for universal use in both mechanical and plant engineering and vehicle engineering.

The EW-PA cable protection conduits feature the following advantages:

- High crush resistance
- Good flexibility
- Medium to high loads in static applications

Information, conformities and approvals



Article	Order No.	Color	UV	metric	PG	NW	A Ø mm	B Ø mm	Stat./Dyn. Radius mm	Weight kg/100m	PU m
EW-PA-4,5	83161051	Black	✓				5	7.1	20/-	1.8	100
EW-PA-06	83161050	Black	✓				6.6	10	21/-	2.2	50
EW-PA-M10/P7	83161052	Black	✓	M10	PG07	NW 7	8.5	11.5	24/-	2.5	50
EW-PA-M12/P9	83161054	Black	✓	M12	PG09	NW 10	9.7	12.9	26/-	2.8	50
EW-PA-M12/P09, Octabin 1) 1**)	83988294	Black	✓	M12	PG09	NW 10	9.7	12.9	26/-	2.8	3000
EW-PA-M16/P11	83161056	Black	✓	M16	PG11	NW 12	12.1	15.9	38/-	3.8	50
EW-PA-M16/P11, Octabin 1) 1**)	83988293	Black	✓	M16	PG11	NW 12	12.1	15.9	38/-	3.8	2300
EW-PA-M20/P16	83161060	Black	✓	M20	PG16	NW 17	15.6	21	55/-	5.8	50
EW-PA-M20/P16, Octabin 1) 1**)	83988292	Black	✓	M20	PG16	NW 17	15.6	21	55/-	5.8	1100
EW-PA-M20/P16S	83162062	Black	✓	M20	PG16	NW 17	16.3	20.7	50/-	6.3	50
EW-PA-M25/P21	83161064	Black	✓	M25	PG21	NW 23	21.8	28.3	64/-	9.0	50
EW-PA-M25/P21, Octabin 1) 1**)	83988291	Black	✓	M25	PG21	NW 23	21.8	28.3	64/-	9.0	700



Type EW-PA

Article	Order No.	Color	UV	metric	PG	NW	A Ø mm	B Ø mm	Stat./Dyn. Radius mm	Weight kg/100m	PU m
EW-PA-M25/P21S83162064		Black	✗	M25	PG21	NW 23	22.9	28.3	59/-	9.0	50
EW-PA-M32/P29 83161072		Black	✓	M32	PG29	NW 29	27.8	34.5	72/-	13.5	25
EW-PA-M32/P29, 83988290 Octabin 1) 1**)		Black	✓	M32	PG29	NW 29	27.8	34.5	72/-	13.5	400
EW-PA-M32/ P29S 83162072		Black	✓	M32	PG29	NW 29	28.5	34.5	67/-	13.5	25
EW-PA-M40/P36 83161076		Black	✓	M40	PG36	NW 36	35	42.6	81/-	15.0	25
EW-PA-M40/ P36S 83162076		Black	✓	M40	PG36	NW 36	36	42.1	76/-	15.0	25
EW-PA-M50/P48 83161078		Black	✓	M50	PG48	NW 48	46.9	53.9	97/-	22.0	25
EW-PA-M50/ P48S 83162080		Black	✓	M50	PG48	NW 48	47.5	54.5	92/-	22.0	25
EW-PA-56 Jumbo 83161081		Black	✓			NW 56	56	67.6	115/-	38.5	25
EW-PA-70 Jumbo 83161082		Black	✓			NW 70	67.4	79.7	160/-	46.0	25
EW-PA-95 Jumbo 83161086		Black	✓			NW 95	89.7	106.3	200/-	80.0	10
EW-PA-06 83161010		Gray	✗				6.6	10	21/-	2.2	50
EW-PA-M10/P7 83161012		Gray	✗	M10	PG07	NW 7	8.5	11.5	24/-	2.5	50
EW-PA-M12/P9 83161014		Gray	✗	M12	PG09	NW 10	9.7	12.9	26/-	2.8	50
EW-PA-M16/P11 83161016		Gray	✗	M16	PG11	NW 12	12.1	15.9	38/-	3.8	50
EW-PA-M20/P16 83161018		Gray	✗	M20	PG16	NW 17	15.6	21	55/-	5.8	50
EW-PA-M20/ P16S 83162020		Gray	✗	M20	PG16	NW 17	16.3	20.7	50/-	6.3	50
EW-PA-M25/P21 83161022		Gray	✗	M25	PG21	NW 23	21.8	28.3	64/-	9.0	50
EW-PA-M25/P21S83162022		Gray	✗	M25	PG21	NW 23	22.9	28.3	59/-	9.0	50
EW-PA-M32/P29 83161026		Gray	✗	M32	PG29	NW 29	27.8	34.5	72/-	13.5	25
EW-PA-M32/ P29S 83162026		Gray	✗	M32	PG29	NW 29	28.5	34.5	67/-	13.5	25
EW-PA-M40/P36 83161028		Gray	✗	M40	PG36	NW 36	35	42.6	81/-	15.0	25
EW-PA-M40/ P36S 83162030		Gray	✗	M40	PG36	NW 36	36	42.1	76/-	15.0	25
EW-PA-M50/P48 83161030		Gray	✗	M50	PG48	NW 48	46.9	53.9	97/-	22.0	25
EW-PA-M50/ P48S 83162034		Gray	✗	M50	PG48	NW 48	47.5	54.5	92/-	22.0	25



Type EW-PA

Article	Order No.	Color	UV	metric	PG	NW	A Ø mm	B Ø mm	Stat./Dyn. Radius mm	Weight kg/100m	PU m
EW-PA-56 Jumbo 3)	83161031	Gray	✗			NW 56	56	67.6	115/-	38.5	25
EW-PA-70 Jumbo	83161032	Gray	✗			NW 70	67.4	79.7	160/-	46.0	25
EW-PA-95 Jumbo 3)	83161034	Gray	✗			NW 95	89.7	106.3	200/-	80.0	10

1) One piece corrugated conduit in the Octabin container
2) With CSA approval
3) No stock goods, delivery time and minimum order quantities upon request
1**) No stock goods, delivery time and minimum order quantities upon request

1) One piece corrugated conduit in the Octabin container
2) With CSA approval
3) No stock goods, delivery time and minimum order quantities upon request
1**) No stock goods, delivery time and minimum order quantities upon request

Material properties

	mod. polyamide PA 6
	High angle consistency >336 N 50 x 50 mm According to IEC EN 61386 M25/P21 Testing at 23 °C >653 N 100 x 100 mm According to IEC EN 61386 M25/P21 Testing at 23 °C
	Flexural fatigue strength >24000 Cycles According to IEC EN 61386 M25/P21 Testing at -25 °C
	Impact strength 4.5 According to IEC EN 61386 M25/P21 Testing at -25 °C
	System tear-out strength >350 N According to IEC EN 61386 M25/P21 Testing at 23 °C Fitting M-PRO

Thermal properties

	Temperature / temperature range -40 °C - 120 °C / short term: 160 °C
--	---

Fire properties

	Fire classification acc. to UL94: HB
--	---



Type EW-PA

Chemical resistances



Resistant to:

Alcohol
Mineral oils
Greases
Fuels

Technical information



Halogen-free



According to ISO 4892-2

Approvals and operating permits



ECOLAB approval

Classification

ETIM 9: EC001175
ECLASS 14: 27430305
UNSPSC 26.0801: 39131601

General information



Made in Germany