



Edge protection profile with serrated edge type KSP-Z



Product information

The edge protection profile with serrated edge protects cables from sharp edges in control cabinets and sheet metal passages. It can be flexibly adjusted in length and only needs to be pressed onto the edge of the sheet.


- Polyethylene is flame-retardant
- Tensile strength: >10 MPa
- Crack resistance: >600%
- Impact resistance: 60 kV/mm
- Chemical resistance: very good

Information, conformities and approvals




Article	Order No.	Color	sheet thickness from - to mm	Length mm	PU pcs.
KSP-Z 1,5	87621810	White	1,2 - 1,7	30	30
KSP-Z 2,0	87621811	White	1,7 - 2,5	25	25

Thermal properties



Fire properties



Classification

ETIM 9: —
ECLASS 14: —
UNSPSC 26.0801: 39131605

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.