




Type WKM-FDA (metal versions)



Product information


The WKM/FDA cable fitting is suitable for use in all areas where the accumulation of microorganisms and dirt must be avoided, for example in the pharmaceutical, food and chemical industries, as well as in biotechnology and cleanroom technology.

The WKM/FDA cable fitting features the following advantages:

- Hygienic Design
- FDA compliant
- EHEDG
- High temperature resistance

*Suitable locknut must be ordered separately.

Information, conformities and approvals



Article	Order No.	Color	Connecting thread	Clamping range (LW) mm	EH mm	GL mm	SW 1 / 2 mm	PU pcs.
WKM/FDA M12x1,5	84241000	Silver	M12x1,5	5 - 6.5	19	6	14 / 14	10
WKM/FDA M16x1,5s	84241004	Silver	M16x1,5	6 - 7.5	20	6	19 / 21	5
WKM/FDA M16x1,5	84241006	Silver	M16x1,5	7.5 - 10	20	6	19 / 21	5
WKM/FDA M20x1,5s	84241010	Silver	M20x1,5	9 - 12	22.5	6	24 / 27	5
WKM/FDA M20x1,5	84241012	Silver	M20x1,5	11 - 13.5	22.5	6	24 / 27	5
WKM/FDA M25x1,5s	84241016	Silver	M25x1,5	14 - 16	23.5	7	30 / 30	5
WKM/FDA M25x1,5	84241018	Silver	M25x1,5	15 - 18	23.5	7	30 / 30	5
WKM/FDA M32x1,5s	84241022	Silver	M32x1,5	18 - 21	26.5	8	36 / 36	5
WKM/FDA M32x1,5	84241024	Silver	M32x1,5	21 - 25	26.5	8	36 / 36	5

Material properties



Fitting: Stainless steel 1.4404
Moulded seal: Silicone Stainless steel 1.4404
Silicone



Type WKM-FDA (metal versions)

Thermal properties



Temperature / temperature range

-40 °C – 100 °C / short term: 120 °C

Protection class



Protection class

IP66

IP68 up to 10 bar

IP69K

Chemical resistances



Resistant to:

Alcohol

Greases

Fuels

Mineral oils

Approvals and operating permits



FDA compliance

Classification

ETIM 9: EC000441

ECLASS 14: 27140801

UNSPSC 26.0801: 39131711

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

Recommended torques for **murrplastik connectors, corrugated conduits and cable fittings**



holders, lock nuts and reducers





Recommended torques for **murrplastik connectors, corrugated conduits and cable fittings, holders, lock nuts and reducers**

Fastening with lock nut

Metric thread EN 60423	Connecting thread and lock nut made of polyamide	Connection thread and lock nut made of metal
M12x1.5	2.0 Nm	5.0 Nm
M16x1.5	3.0 Nm	7.0 Nm
M20x1.5	4.0 Nm	8.0 Nm
M25x1.5	5.0 Nm	10.0 Nm
M32x1.5	6.0 Nm	12.0 Nm
M40x1.5	11.0 Nm	16.0 Nm
M50x1.5	15.0 Nm	17.0 Nm
M63x1.5	16.0 Nm	18.0 Nm

Pg thread DIN 40430	Connecting thread and lock nut made of polyamide	Connection thread and lock nut made of metal
Pg 7	2.0 Nm	4.0 Nm
Pg 9	2.5 Nm	4.0 Nm
Pg 11	3.5 Nm	6.0 Nm
Pg 13.5	4.0 Nm	7.0 Nm
Pg 16	4.5 Nm	8.0 Nm
Pg 21	7.5 Nm	10.0 Nm
Pg 29	9.0 Nm	13.0 Nm
Pg 36	14.0 Nm	15.0 Nm
Pg 42	15.0 Nm	16.0 Nm
Pg 48	16.0 Nm	17.0 Nm

Please note the following information:

- The specified tightening torques are maximum values and should not be exceeded.
- The values are based on measurements under normal climate conditions (23°C / 50% rel. humidity). During assembly and operation, the prevailing climatic conditions should also be taken into account, as these can affect the properties of the components.
- Please consider the properties of the other components with which the murrplastik elements are connected.
- Locking and sealing elements tightened with a lower torque provide better long-term strength.



Recommended torques for **Screws and nuts**

Torques for screws and nuts

Thread size	Torques
M4	2.0 Nm
M5	3.0 Nm
M6	4.0 Nm
M8	10.0 Nm
M10	15.0 Nm

Product examples from our webshop range



Series m-pro

on to the product

shop.murrplastik.de



Series m-fix

on to the product

shop.murrplastik.de



UHE Holder

on to the product

shop.murrplastik.de

More info at

shop.murrplastik.de

**Murrplastik
Systemtechnik GmbH**

Dieselstraße 10
71570 Oppenweiler
Germany

Phone: +49 7191 4820
info@murrplastik.de

Managing Directors:
Jürgen Zeltwanger (CEO)
Gerd Nothdurft (COO)

HRB 271053 Local court Stuttgart
VAT ID: DE 144 744 122



MP8902834212

23



0601HS

More info at

murrplastik.de