

Cable entry grommet type KDT/P-Ex







Product information

Cable entry grommet for pre-assembled cables in connection with cable entry system KDP/P-Ex

The grommets are retrofitted around the cable.
Thermal stability: -40 °C – +70 °C
Fire classification: HB
Material: TPE
RoHS compliant
UV resistant
Made in Germany

Information, conformities and approvals

Article	Order No.	Color	for Ø mm	No. of openings	PU pcs.
KDT/P-Ex 03	87351202	Yellow	3	1	4
KDT/P-Ex 04	87351204	Yellow	4	1	4
KDT/P-Ex 05	87351206	Yellow	5	1	4
KDT/P-Ex 06	87351208	Yellow	6	1	4
KDT/P-Ex 07	87351210	Yellow	7	1	4
KDT/P-Ex 08	87351212	Yellow	8	1	4
KDT/P-Ex 09	87351214	Yellow	9	1	4
KDT/P-Ex 10	87351216	Yellow	10	1	4
KDT/P-Ex 11	87351218	Yellow	11	1	4
KDT/P-Ex 12	87351220	Yellow	12	1	4
KDT/P-Ex BTK	87351250	Yellow			4

Cable entry grommet type KDT/P-Ex

Thermal properties

Temperature / temperature range

-40 °C – 70 °C

Protection class

Protection class

IP65 (with suitable grommets and cables)
(with suitable grommets and cables)

Fire properties

Fire classification

HB

Technical information

Halogen-free

LABS free

Conformity

RoHS (EC Directive 2011/65/EU)

Approvals and operating permits

EX approval

ECOLAB approval

cURus approval

IECEx approval

Classification

ETIM 9: EC002624
ECLASS 14: 27182815

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.
The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.
A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.
All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.
They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.
Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.
Murrplastik accepts no liability for damage caused as a result of using our products.
Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.
Our General Terms and Conditions apply.