

## BT label holder



### Product information

The BT and BTK label holders are used for labeling non-proprietary components and assemblies.

Fastened with self-tapping screws.

Self-adhesive film is supplied with the BTK version as an installation aid.

The transparent cover keeps the inserted label plates clean and free from mechanical load.

### Information, conformities and approvals



Article	Order No.	Color	Recommended Label	PU pcs.
<b>Label holder</b>				
BT 15/27	86441010	Black	KS 15/27	250
BT 15/49	86441012	Black	KS 15/49	250
BT 15/67	86441014	Black	KS 15/67	250
<b>Label holder with adhesive strip on the back</b>				
BTK 15/27	86441210	Black	KS 15/27	250
BTK 15/49	86441212	Black	KS 15/49	250
BTK 15/67	86441214	Black	KS 15/67	250
<b>Label holder for Ø 22.5 mm elements</b>				
BT 22.5	86442018	Black	KS 8/26.5	250
<b>Label holder for elements with Ø 22.5 mm, with adhesive strip on the back</b>				
BTK 22.5	86441016	Black	KS 15/27	250
<b>Label holder for Moeller elements with Ø 28 mm</b>				



## BT label holder

Article	Order No.	Color	Recommended Label	PU pcs.
BT Harmony ZB4	86442016	Black	KS 8/26.5	250
<b>Transparent cover for label holder</b>				
TA 8/26.5	86441418	Transparent		480
TA 15/27	86441410	Transparent		480
TA 15/49	86441412	Transparent		240
TA 15/67	86441414	Transparent		120

### Material properties



BT and BTK Polyamide 6.6 (PA 6.6)  
TA: Polycarbonate (PC) Polyamide 6.6 (PA 6.6)  
Polycarbonate (PC)

### Adhesive properties



9088BTK with adhesive:

### Thermal properties



Temperature / temperature range  
-40 °C - 80 °C

### Fire properties



Fire classification  
V0

### Classification

ETIM 9: EC000141  
ECLASS 14: 27144009  
UNSPSC 26.0801: 39131504

### General technical data



Assembly method  
0000000000110



---

## BT label holder

---

### Assembly method



Riveting system



Screw system

---