

FHS Retraction system 21/29




Product information

The retraction system is a simple and space-saving system and can handle a length adjustment of 150 mm. The system is used on small robots such as UR5 & UR10 from Universal Robots.

The retraction system can be mounted directly on the robot with FHS-hook-and-loop holders.

Information, conformities and approvals



Article	Order No.	Color	Stroke mm	Suitable for EW-PAE	Suitable for EWX-PAE	PU pcs.
FHS-RS EW 21 - 20N 1)	83693411	Black	150	M25/P21		1
FHS-RS EWX 21 - 20N 1)	83693412	Black	150		M25/P21	1
FHS-RS EW 29 - 20N 1)	83693413	Black	150	M32/P29		1
FHS-RS EWX 29 - 20N 1)	83693414	Black	150		M32/P29	1

1) The set includes the hook-and-loop tape lengths 350mm and 450mm.

1) The set includes the hook-and-loop tape lengths 350mm and 450mm.

Material properties



Base plate Aluminium
Spring Steel mod. polyamide PA 6
Aluminium
Steel

Thermal properties



Temperature / temperature range
-40 °C - 110 °C

FHS Retraction system 21/29

Fire properties



Fire classification
acc. to UL94: V0

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



ROBI approval

Classification

ETIM 9: EC010745
ECLASS 14: 27439090
UNSPSC 26.0801: 40141764

General information



Made in Germany