




Cable entry system type KDL/D FDA



Product information

2-piece or 3-piece frame

Easy assembly

For use in the food and pharmaceutical sectors

Protection class: IP 65 (with suitable grommets and cables)

Thermal stability: -40°C - +80°C

Material: Frame: PP / Block: TPE

RoHS compliant

Made in Germany

Suitable for standard cut-outs for 24-pin and 16-pin industrial connectors as well as one special size (single row)

Suitable grommets: KDT/X-FDA

Information, conformities and approvals




Article	Order No.	for Ø mm	No. of openings small / medium / large	Diameter mm small / large	For opening small / medium / large	No. of openings	Material	Cut-out	PU pcs.
For standard cut-out size 24									
KDL/D 24/12-FDA, ws/bl, Set	87142710	2 - 12	12 / 0 / 0	2 / 12	yes / no / no	12	mod. polypropylene	24-pole	1
KDL/D 24/4-FDA Set	87142714	12 - 22	0 / 4 / 0	12 / 22	no / yes / no	4	mod. polypropylene	24-pole	1
KDL/D 24/3-FDA Set	87142713	12 - 30	0 / 1 / 2	12 / 30	no / yes / yes	3	mod. polypropylene	24-pole	1



Cable entry system type KDL/D FDA

Article	Order No.	for Ø mm	No. of openings small / medium / large	Diameter mm small / large	For opening small / medium / large	No. of openings	Material	Cut-out	PU pcs.
For standard cut-out size 16									
KDL/D 16/8-FDA Set 87142726		2 - 12	8 / 0 / 0	2 / 12	yes / no / no	8	mod. polypropylene 16-pole		1
KDL/D 16/3-FDA Set 87142734		12 - 22	0 / 3 / 0	12 / 22	no / yes / no	3	mod. polypropylene 16-pole		1
KDL/D 16/2-FDA Set 87142733		22 - 30	0 / 0 / 2	22 / 30	no / no / yes	2	mod. polypropylene 16-pole		1
Special size									
KDL/D 1/6-FDA Set 87142748		2 - 12	6 / 0 / 0	/	yes / no / no	6	mod. polypropylene		1



Article	Order No.	Installation height (EH) mm	A mm	B mm	a mm	b mm	c mm	d mm	e mm
KDL/D 24/12-FDA, ws/bl, Set	87142710	18	148	58	112	36	65	16	5.5
KDL/D 24/4-FDA Set 87142714		18	148	58	112	36	65	16	5.5
KDL/D 24/3-FDA Set 87142713		18	148	58	112	36	65	16	5.5
For standard cut-out size 16									
KDL/D 16/8-FDA Set 87142726		18	121	58	86	36	51.5	16	5.5
KDL/D 16/3-FDA Set 87142734		18	121	58	86	36	51.5	16	5.5
KDL/D 16/2-FDA Set 87142733		18	121	58	86	36	51.5	16	5.5
Special size									
KDL/D 1/6-FDA Set 87142748		18	148	38	112	17	65		5.5



Cable entry system type KDL/D FDA

Thermal properties



Temperature / temperature range

-40 °C - 80 °C

Protection class



Protection class

IP65 (with suitable grommets and cables)

Technical information



Halogen-free

Assembly method



Strain relief



Approvals and operating permits



FDA compliance



ECOLAB approval

Classification

ETIM 9: EC002624
ECLASS 14: 27182815
UNSPSC 26.0801: 39121312

General information



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.