




ALM Rectangular with radius



Product information

- Triple-layer material (aluminum-plastic-aluminum)
- Black plastic inner layer
- Outer layer in silver or gold
- Available with self-adhesive foil / adhesive foil
- Thickness: 1.5 mm
- Inscription technique: Engraving

Information, conformities and approvals





Article	Order No.	Color	Label size mm	Material thickness mm	Quantity per mat	Software Article	PU pcs.				
Corner radius 2 mm; with adhesive foil											
ALM 12x62 R2 SK	8603100007	Silver / Black / Silver	12 x 62	1.5	75	M80	75				
ALM 30x15 R2 HF	8603106002	Silver / Black / Silver	30 x 15	1.5	130	K99	130				
ALM 45x76 R2 HF	8603106001	Silver / Black / Silver	45 x 76	1.5	12	J44	12				
Corner radius 2 mm; with self-adhesive foil											
ALM 20x10 R2 SK	8603100008	Silver / Black / Silver	20 x 10	1.5	300	Z28	300				
ALM 70x18 R2 SK 1)	8603100003	Silver / Black / Silver	70 x 18	1.5	44	L77	44				
ALM 70x26 R2 SK	8603100004	Silver / Black / Silver	70 x 26	1.5	28	L78	28				
ALM 70x42 R2 SK	8603100005	Silver / Black / Silver	70 x 42	1.5	16	L79	16				
ALM 74x87 R2 SK 1)	8603100002	Silver / Black / Silver	74 x 87	1.5	8	К97	8				
ALM 80x18 R2 SK 1)	8603100001	Silver / Black / Silver	80 x 18	1.5	33	D75	33				
ALM 214x70 R2 SK	8603100006	Silver / Black / Silver	214 x 70	1.5	2	L80	2				
Corner radius 4 mn	Corner radius 4 mm; with high-strength adhesive foam foil										

© Murrplastik Systemtechnik GmbH • 1 as of 2025-10-14 - 174827





ALM Rectangular with radius

Article	Order No.	Color	Label size mm	Material thickness mm	Quantity per mat	Software Article	PU pcs.
ALM 59x11.5 R4 SKS	8603102001	Silver / Black / Silver	59 x 11.5	1.5	85	Z15	85

1) Other sizes available on request

1) Other sizes available on request

Material properties



Alumatt (ALM)

Adhesive properties



467SK adhesive film with adhesive

Thermal properties



Temperature / temperature range

-40 °C - 80 °C

Fire properties



Fire classification

B2

Classification

ETIM 9: EC001288 ECLASS 14: 27144009 UNSPSC 26.0801: 39131504

General technical data



Assembly method

0000001Label glued into place 00000

Assembly method



Adhesive system





ALM Rectangular with radius

Labelling technology



Engraving

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the product described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.