



Cable entry grommet type KDT/Z-Jumbo



Product information

2-piece cable entry grommet in connection with cable entry system KDL-Jumbo

With our grommet KDT/Z- Jumbo cables from 25-65 mm can be inserted
Grommet is placed and mounted together with the frame halves of the KDL-Jumbo around the cable
Quick and easy strain relief with cable ties is possible

Thermal stability: -30 °C – +100 °C

Fire classification: V0

Material: TPE-S

RoHS compliant

UV resistant

Made in Germany

Information, conformities and approvals



Article	Order No.	Color	for Ø mm	No. of openings	PU pcs.
	87176226	Black	25 - 30	1	1
KDT/Z-Jumbo 30-35	87176212	Black	30 - 35	1	1
KDT/Z-Jumbo 35-40	87176214	Black	35 - 40	1	1
KDT/Z-Jumbo 40-45	87176216	Black	40 - 45	1	1
KDT/Z-Jumbo 45-50	87176218	Black	45 - 50	1	1
KDT/Z-Jumbo 50-55	87176220	Black	50 - 55	1	1
KDT/Z-Jumbo 55-60	87176222	Black	55 - 60	1	1
KDT/Z-Jumbo 60-65	87176224	Black	60 - 65	1	1
Dummy grommet					
BT-Jumbo	87176210	Black			1



Cable entry grommet type KDT/Z-Jumbo

Material properties



TPE-S

Thermal properties



Temperature / temperature range

-30 °C - 100 °C / short term: -65 °C

Fire properties



Fire classification

acc. to UL94: V0

Technical information



Halogen-free



LABS free



According to ISO 4892-2

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



cURus approval

Classification

ETIM 9: EC002624
ECLASS 14: 27182815

General information



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.
The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.
A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.
All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.
They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.
Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.
Murrplastik accepts no liability for damage caused as a result of using our products.
Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.
Our General Terms and Conditions apply.