

FHS-SH support bracket



Product information

The FHS-SH fixes the proven SH-P M25-M32 system holder without tools and without much effort to nearly any small robots and cobots. For smaller cable packages and low to medium travel speed, this is the way to provide secure hold and maximum flexibility for the applications. The respective protective conduits can be installed fixed, sliding in axial direction or with strain relief by using additional system components in M25 or M32 sizes.

Optional accessories:

- KEG/ZL - strain relief with cable ties
- KEG/K - strain relief with cable star
- KMG/G - sliding channel guide
- KMG/F - axial channel guide

Information, conformities and approvals



Article	Order No.	Color	Length of hook-and-loop tape mm	Clamping range C mm	PU pcs.
FHS-SH-G 1)	83693416	Black / Red			1
FHS-SH 300	83693424	Black / Red	300	45 - 60	1
FHS-SH 350	83693423	Black / Red	350	55 - 80	1
FHS-SH 450	83693425	Black / Red	450	75 - 110	1
FHS-SH 550	83693427	Black / Red	550	95 - 140	1
FHS-SH 650	83693428	Black / Red	650	110 - 175	1
FHS-SH 750	83693429	Black / Red	750	125 - 205	1
FHS-SH Set 2)	83693422	Black / Red	350 - 750	55 - 205	1

1) Body without hook-and-loop tape
2) Set with 4 hook-and-loop tapes

1) Body without hook-and-loop tape
2) Set with 4 hook-and-loop tapes

FHS-SH support bracket

Material properties



mod. polyamide
mod. polypropylene
Thermoplastic elastomer

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



ROBI approval

Classification

ETIM 9: EC000449
ECLASS 14: 23152522
UNSPSC 26.0801: 39121717

General information



Made in Germany