

Type GF-P (braided conduit)



Product information

The GF-P braided conduits are made of specially modified polyester. With this material and the special braiding, the conduit is extremely durable and elastic in both the radial and axial directions.

It can be used to bundle and protect a large number of cables and individual wires of all types. The elastic braiding means that configuration of the conduit can be very variable.

The SAT-GF conduit connection serves as an end piece for the braided conduits.

Additional advantages of the GF-P braided conduit include:

- Very good mechanical and thermal resistance
- Good chemical resistance
- Very low levels of smoke gas
- Very high abrasion resistance

Information, conformities and approvals



Article	Order No.	Color	UV	Nominal width NW	Suitable for SAT-GF	Size range mm	Surface covering in %	Weight kg/100m	PU m
GF-P 3	83342008	Black	✓	4		2 / 6	93	0.41	200
GF-P 4	83342010	Black	✓	4		3 / 7	93	0.58	200
GF-P 6	83342012	Black	✓	6		5 / 9	86	0.7	200
GF-P 8	83342014	Black	✓	8		7 / 12	87	0.74	200
GF-P 10	83342016	Black	✓	10	SAT-GF M16/P11	8 / 15	77	0.91	200
GF-P 12	83342018	Black	✓	12	SAT-GF M16/P11	8 / 15	74	0.94	200
GF-P 16	83342020	Black	✓	16	SAT-GF M20/P16	12 / 24	80	1.5	100
GF-P 20	83342022	Black	✓	20	SAT-GF M20/P16	16 / 32	75	1.75	100
GF-P 22	83342024	Black	✓	22	SAT-GF M25/P21	18 / 33	84	1.9	100
GF-P 30	83342026	Black	✓	30	SAT-GF M32/P29	28 / 37	78	2.65	100
GF-P 40	83342028	Black	✓	40	SAT-GF M40/P36	32 / 45	77	3.18	50
GF-P 50	83342030	Black	✓	50	SAT-GF M50/P48	30 / 55	79	3.88	50
GF-P 70	83342032	Black	✓	70		60 / 88	87	5.94	50



Type GF-P (braided conduit)

Article	Order No.	Color	UV	Nominal width NW	Suitable for SAT-GF	Size range mm	Surface covering in %	Weight kg/100m	PU m
GF-P 4	83342050	Gray	✗	4		3 / 7	93	0.58	200
GF-P 6	83342052	Gray	✗	6		5 / 9	86	0.7	200
GF-P 8	83342054	Gray	✗	8		7 / 16	87	0.74	200
GF-P 10	83342056	Gray	✗	10	SAT-GF M16/P11	8 / 15	77	0.91	200
GF-P 12	83342058	Gray	✗	12	SAT-GF M16/P11	8 / 15	74	0.94	200
GF-P 16	83342060	Gray	✗	16	SAT-GF M20/P16	12 / 24	80	1.5	100
GF-P 20	83342062	Gray	✗	20	SAT-GF M20/P16	16 / 32	75	1.75	100
GF-P 22	83342064	Gray	✗	22	SAT-GF M25/P21	18 / 33	84	1.9	100
GF-P 30	83342066	Gray	✗	30	SAT-GF M32/P29	28 / 37	78	2.65	100
GF-P 40	83342068	Gray	✗	40	SAT-GF M40/P36	32 / 45	77	3.18	50
GF-P 50	83342070	Gray	✗	50	SAT-GF M50/P48	30 / 55	79	3.88	50
GF-P 70	83342072	Gray	✗	70		60 / 88	87	5.94	50

Material properties



mod. polyester

Thermal properties



Temperature / temperature range

-55 °C - 150 °C / short term: 175 °C

Fire properties



Fire classification

acc. to UL94: V2 self-extinguishing



Fire properties as per EN 45545-2

C.I.T. R22 / R23 HL3 :0.1 NF X 70-100-1/-2 600 °C (1112 °F)

LOI R22 / R23 HL3 :34.5 ISO 4589-2

Ds (max.) R22 / R23 HL3 :132 ISO 5659-2 (25 KW/m²)



Type GF-P (braided conduit)

Chemical resistances



Resistant to:
Alcohol
Greases
Fuels
Weak acids

Technical information



Halogen-free

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



EU railway approval

Classification

ETIM 9: EC001182
ECLASS 14: 27430303
UNSPSC 26.0801: 40183009

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.