



Type GF (braided conduit)



Product information

The GF braided conduits are made of specially modified polyamide 6.6. With this material and the special braiding, the conduit is extremely durable and elastic in both the radial and axial directions.

The GF braided conduit is used to bundle and protect a large number of cables and individual wires of all types. The elastic braiding means that configuration of the conduit can be very variable.

The SAT-GF conduit connection serves as an end piece for the braided conduits.

Additional advantages of the GF braided conduit include:

- Very good mechanical and thermal resistance
- Good chemical resistance
- High flexibility
- Very high abrasion resistance



Information, conformities and approvals



Article	Order No.	Color	Nominal width NW	Suitable for SAT-GF	Size range mm	Surface covering in %	Weight kg/100m	PU m
GF 4 1) 1**)	83341010	Black	4		3 / 7	93	0.7	200
GF 6 1)	83341012	Black	6		5 / 9	86	0.7	200
GF 8 1)	83341014	Black	8	SAT-GF M16/P11	7 / 16	87	1.0	200
GF 10 1)	83341016	Black	10	SAT-GF M16/P11	8 / 15	77	1.3	200
GF 12 1)	83341018	Black	12	SAT-GF M16/P11	8 / 15	74	1.6	200
GF 16 1)	83341020	Black	16	SAT-GF M20/P16	12 / 24	80	1.7	100
GF 20 1)	83341022	Black	20	SAT-GF M25/P21	16 / 32	75	2.5	100
GF 22 1)	83341024	Black	22	SAT-GF M25/P21	18 / 33	84	2.6	100
GF 30 1)	83341026	Black	30	SAT-GF M32/P29	28 / 37	78	2.5	100
GF 40 1)	83341028	Black	40	SAT-GF M40/P36	32 / 45	77	4.0	50
GF 50 1)	83341030	Black	50	SAT-GF M50/P48	30 / 55	79	5.0	50
GF 70 1) 1**)	83341072	Gray	70		60 / 88	84	5.95	50

1) Discontinued product!



Type GF (braided conduit)

Article	Order No.	Color	Nominal width NW	Suitable for SAT-GF	Size range mm	Surface covering in %	Weight kg/100m	PU m
---------	-----------	-------	---------------------	------------------------	------------------	-----------------------------	-------------------	------

1**) No stock goods, delivery time and minimum order quantities upon request

1) Discontinued product!

1**) No stock goods, delivery time and minimum order quantities upon request

Material properties



mod. polyamide PA 6.6

Thermal properties



Temperature / temperature range

-55 °C - 125 °C / short term: 150 °C

Fire properties



Fire classification

acc. to UL94: V2 self-extinguishing

Chemical resistances



Resistant to:

Fuels
Greases
Mineral oils

Technical information



Halogen-free

Conformity



RoHS (EC Directive 2011/65/EU)

Classification

ETIM 9: EC001182
ECLASS 14: 27430303

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.