





Cable entry plate round type KDP/ZR



Product information

The KDP/ZR cable entry plate is made of modified Polypropylene and is a round entry and fastening system for cables without plugs and pneumatic hoses such as those used in control cabinets, plant or machine construction. Wherever quick assembly is required with high packing density and cables must be protected, the cable insertion system is used. The special benefits of the KDP/ZR are:

- Enormous time savings in assembly
- High packing density
- Standardized cut-out dimensions
- Large wire diameter ranges
- Very flat design



Information, conformities and approvals



Article	Order No.	Color	No. Openings	Openings Quantity / Ø mm	Thread metric	PU pcs.
small thread						
KDP/ZR 40/6, KG	87303130	Black	6	1x 2 mm - 4 mm 2x 3 mm - 6 mm 2x 5 mm - 9 mm 1x 7.5 mm - 12 mm	M40x1,5	5
KDP/ZR 40/7, KG	87303132	Black	7	4x 3 mm - 6 mm 3x 5 mm - 9 mm	M40x1,5	5
KDP/ZR 50/10, KG	87303150	Black	10	2x 2 mm - 4 mm 3x 3 mm - 6 mm 3x 5 mm - 9 mm 1x 7.5 mm - 12 mm 1x 10 mm - 16 mm	M50x1,5	5
KDP/ZR 50/10-1, KG	87303152	Black	10	3x 3 mm - 6 mm 7x 5 mm - 9 mm	M50x1,5	5
KDP/ZR 63/15, KG	87303170	Black	15	4x 2 mm - 4 mm 3x 3 mm - 6 mm 4x 5 mm - 9 mm 2x 7.5 mm - 12 mm 1x 10 mm - 16 mm 1x 14 mm - 20 mm	M63x1,5	5
KDP/ZR 63/18, KG	87303172	Black	18	8x 3 mm - 6 mm 10x 5 mm - 9 mm	M63x1,5	5
KDP/ZR 63/30, KG	87303174	Black	30	30x 3 mm - 6 mm	M63x1,5	5
Standard thread						





Cable entry plate round type KDP/ZR

Article	Order No.	Color	No. Openings	Openings Quantity / Ø mm	Thread metric	PU pcs.
KDP/ZR 40/6	87303120	Black	6	1x 2 mm - 4 mm 2x 3 mm - 6 mm 2x 5 mm - 9 mm 1x 7.5 mm - 12 mm	M40x1,5	5
KDP/ZR 40/7	87303122	Black	7	4x 3 mm - 6 mm 3x 5 mm - 9 mm	M40x1,5	5
KDP/ZR 50/10	87303140	Black	10	2x 2 mm - 4 mm 3x 3 mm - 6 mm 3x 5 mm - 9 mm 1x 7.5 mm - 12 mm 1x 10 mm - 16 mm	M50x1,5	5
KDP/ZR 50/10-1	87303142	Black	10	3x 6 mm - 9 mm 7x 5 mm - 9 mm	M50x1,5	5
KDP/ZR 63/15	87303160	Black	15	4x 2 mm - 4 mm 3x 3 mm - 6 mm 4x 5 mm - 9 mm 2x 7.5 mm - 12 mm 1x 10 mm - 16 mm 1x 14 mm - 20 mm	M63x1,5	5
KDP/ZR 63/18	87303162	Black	18	8x 3 mm - 6 mm 10x 5 mm - 9 mm	M63x1,5	5
KDP/ZR 63/30	87303164	Black	30	30x 3 mm - 6 mm	M63x1,5	5



Cable entry plate round type KDP/ZR



Cable entry plate KDP plastic round

Article	Order No.	Installation height mm	A mm	B mm	C mm	d mm
small thread						
KDP/ZR 40/6, KG	87303130	8.5	48.5	8.5	12	40.5
KDP/ZR 40/7, KG	87303132	8.5	48.5	8.5	12	40.5
KDP/ZR 50/10, KG	87303150	8.5	58.5	8.5	12	50.5
KDP/ZR 50/10-1, KG	87303152	8.5	58.5	8.5	12	50.5
KDP/ZR 63/15, KG	87303170	8.5	71.5	8.5	12	63.5
KDP/ZR 63/18, KG	87303172	8.5	71.5	8.5	12	63.5
KDP/ZR 63/30, KG	87303174	8.5	71.5	8.5	12	63.5
Standard thread						
KDP/ZR 40/6	87303120	8.5	48.5	8.5	24.5	40.5
KDP/ZR 40/7	87303122	8.5	48.5	8.5	24.5	40.5
KDP/ZR 50/10	87303140	8.5	58.5	8.5	24.5	50.5
KDP/ZR 50/10-1	87303142	8.5	58.5	8.5	24.5	50.5
KDP/ZR 63/15	87303160	8.5	71.5	8.5	24.5	63.5
KDP/ZR 63/18	87303162	8.5	71.5	8.5	24.5	63.5
KDP/ZR 63/30	87303164	8.5	71.5	8.5	24.5	63.5

Material properties



Polypropylene (PP) | Thermoplastic elastomer (TPE) |

Thermal properties



Temperature / temperature range -45 °C – 70 °C



Cable entry plate round type KDP/ZR

Protection class



Protection class IP66/67, IP69K (with matching cables)

Fire properties



Fire classification HB

Technical information



LABS free



According to ISO 4892-2



exterior

Conformity



RoHS (EC Directive 2011/65/EU)

General information



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.