

KCE-ECO single wire labeling



Product information

The KCE-ECO label plates are made of PE composite material on a transparent carrier film and a 3° core; they can be used as an alternative to the PC labels in the KS series.


Each of the individual labels is 4 mm wide and available in lengths of 12 mm, 18 mm, 23 mm or 30 mm.

In addition to the label length, there is a 10 mm section for bending, which can also be used to print additional information.

The plate is bent by 180° at the bending point and pushed into the sleeve, where it is then held in place by bracing.

Suitable formp-TM series thermal transfer printers.

Information, conformities and approvals



Article	Order No.	Color	Sheet size mm	Number of columns	Roll width mm	Recommended Colour ribbon	Software Article	PU pcs.
KCE-ECO 4x12	86513000	White	12 x 4	1	104	FB-TM 110 mm x 300 m	QA0	10000
KCE-ECO 4x18	86513001	White	18 x 4	1	104	FB-TM 110 mm x 300 m	QA1	10000
KCE-ECO 4x23	86513002	White	23 x 4	1	104	FB-TM 110 mm x 300 m	QA2	10000
KCE-ECO 4x30	86513003	White	30 x 4	1	104	FB-TM 110 mm x 300 m	QA3	10000

Material properties



Polyethylene (PE)

Thermal properties



Temperature / temperature range

-40 °C - 90 °C



KCE-ECO single wire labeling

Technical information



Halogen-free



Silicone-free



Interior

Classification

ETIM 9: EC001530
ECLASS 14: 27281102
UNSPSC 26.0801: 39131504

General technical data



High tensile strength and tear resistance
In compliance with the requirements of REACH and RoHS



High tensile strength and tear resistance
In compliance with the requirements of REACH and RoHS

Labelling technology



Thermal transfer