



Cable entry system type KDL/H-VA FDA




Product information

The corrosion-free cable entry system for the insertion of pre-assembled cables in a very stable and robust design made of stainless steel and FDA compliant material for the food industry.

- 2-piece or 3-piece frame
- Easy assembly from front
- High packing density for up to 12 cables
- Resistant to hydrogen peroxide (35%-H₂O₂)
- Integrated strain relief
- Made of FDA compliant material especially for the food industry
- Suitable for standard cut-outs for 24-pin and 16-pin industrial connectors
- Suitable grommets: KDT/X-FDA


Information, conformities and approvals



Article	Order No.	No. of openings small / medium / large	Diameter mm smallest / largest	Material	Frame material	Cut-out	PU pcs.
For standard cut-out size 24							
KDL/H-VA-FDA 24/12, Set 87141882		12 / 0 / 0	2 / 12	VA	Stainless steel	24-pole	1
KDL/H-VA-FDA 24/4, Set 87141880		0 / 4 / 0	12 / 22	VA	Stainless steel	24-pole	1
KDL/H-VA-FDA 24/3, Set 87141878		0 / 1 / 2	12 / 30	VA	Stainless steel	24-pole	1
For standard cut-out size 16							
KDL/H-VA-FDA 16/8, Set 87141877		8 / 0 / 0	2 / 12	VA	Stainless steel	16-pole	1
KDL/H-VA-FDA 16/3, Set 87141874		0 / 3 / 0	12 / 22	VA	Stainless steel	16-pole	1
KDL/H-VA-FDA 16/2, Set 87141875		0 / 0 / 2	22 / 30	VA	Stainless steel	16-pole	1
Special size							
KDL/H-VA-FDA 1/6, Set 87141870		6 / 0 / 0	2 / 12	VA	Stainless steel		1



Cable entry system type KDL/H-VA FDA



Article	Order No.	Installation height (EH) mm	A mm	B mm	a mm	b mm	c mm	d mm	e mm
KDL/H-VA-FDA 24/12, Set	87141882	15	148	58	112	36	65	16	5.5
KDL/H-VA-FDA 24/4, 87141880 Set		15	148	58	112	36	65	16	5.5
KDL/H-VA-FDA 24/3, 87141878 Set		15	148	58	112	36	65	16	5.5
For standard cut-out size 16									
KDL/H-VA-FDA 16/8, 87141877 Set		15	121	58	86	36	51.5	16	5.5
KDL/H-VA-FDA 16/3, 87141874 Set		15	121	58	86	36	51.5	16	5.5
KDL/H-VA-FDA 16/2, 87141875 Set		15	121	58	86	36	51.5	16	5.5
Special size									
KDL/H-VA-FDA 1/6, 87141870 Set		15	148	38	112	17	65	0	5.5

Thermal properties



Temperature / temperature range

-40 °C - 80 °C

Protection class



Protection class

IP69K

Technical information



Halogen-free

Conformity



RoHS (EC Directive 2011/65/EU)



Cable entry system type KDL/H-VA FDA

Approvals and operating permits



FDA compliance



ECOLAB approval

Classification

ETIM 9: EC002624
ECLASS 14: 27182815
UNSPSC 26.0801: 39121312

General information



Made in Germany