



## ALU Rectangular with radius, 6x hole





### Product information


The ALU labeling material, in mat size 300x200 mm, has been developed especially for engraving.

- Coloured anodised aluminium material
- Available with self-adhesive foil / adhesive foil
- Individual or prefab labels
- Temperature range up to approx. 200 °C
- Thickness: 1.0 mm
- marking technique: Engraving

### Information, conformities and approvals



Article	Order No.	Color	Label size mm	Number x Holes mm	Material thickness mm	Quantity per mat	Software Article	PU pcs.
<b>Corner radius of 5 mm; without adhesion</b>								
ALU 250x55 R5, 6x4.5MM (E) 1)	8604998000	Black anodized	250 x 55	6x 4.5	1	1	A43	2
1) Other sizes available on request								
1) Other sizes available on request								



Article	Order No.	Drill hole pitch X mm	Drill hole pitch Y mm	Drill hole position X1 mm	Drill hole position Y1 mm	Drill hole position X2 mm	Drill hole position Y2 mm	Drill hole position X3 mm
ALU 250x55 R5, 6x4.5MM (E) 1)	8604998000	120	45	5	5	125	50	245
1) Other sizes available on request								



## ALU Rectangular with radius, 6x hole

### Material properties



Aluminium anodised (ALU)

### Adhesive properties



467SK adhesive film with adhesive

### Thermal properties



Temperature / temperature range

-40 °C - 140 °C

### Fire properties



Fire classification

V0

### Classification

ETIM 9: EC001288

ECLASS 14: 27144009

UNSPSC 26.0801: 39131504

### General technical data



Assembly method

00000001Label glued into place 0001Mounting the label with screws 0

### Assembly method



Adhesive system



Screw system

### Labelling technology



Engraving