



## Cable entry membrane type KDM/G





### Product information

KDM/G is a cable entry system for cables without plug connectors. The various sizes fit on metric cut-outs from M12 to M50 and are specially designed for cable diameters 4 – 35 mm.

- Easy no-tool push-fit installation
- Extremely high tightness IP66/67
- Fits on standard cut-outs of M12 to M50
- High temperature stability

### Information, conformities and approvals



Article	Order No.	Color	for Ø mm	EH mm	TL mm	D mm	PU pcs.
KDM/G M12	87401020	Gray	4 - 7	7	13	12.2	50
KDM/G M16	87401022	Gray	5 - 10	7	18	16.2	50
KDM/G M20	87401024	Gray	8 - 13	7	20	20.4	50
KDM/G M25	87401026	Gray	11 - 17	7	21.5	25.4	50
KDM/G M32	87401028	Gray	15 - 21	7	25	32.5	25
KDM/G M40	87401030	Gray	19 - 27	8	30	40.5	25
KDM/G M50	87401032	Gray	28 - 35	9.5	35	50.5	10

### Material properties



EPDM

### Thermal properties



Temperature / temperature range

-40 °C – 110 °C



## Cable entry membrane type KDM/G

### Protection class



Protection class

IP66 for plate thickness of 1.0–4.0 mm  
IP67 for plate thickness of 1.0–4.0 mm

### Technical information



Halogen-free



LABS free



UV-resistant acc. to ISO 4892-2

### Conformity



RoHS (EC Directive 2011/65/EU)

### Classification

ETIM 9: EC000879  
ECLASS 14: 27144031  
UNSPSC 26.0801: 39121719