



## Type m-seal EMC (EMV)



### Product information

With the m-seal EMC (EMV) cable fittings, simple radial and axial movement of the cable are possible, even at contact location. The contact finger surfaces with rounded edges prevent damage to the conductor.

In addition, the large surface on the contact finger makes low contact resistance possible, even on loosely woven cables (the contact area does not press into the conductor).

The m-seal EMC (EMV) cable fitting features the following advantages:

- Large seal and clamping area
- With integrated strain relief
- High protection class IP 68
- High contract rating, even at vibration conditions
- Very simple and rapid assembly without tools
- Suitable for the highest requirements of today's technology
- Very good shielding attenuation

\*Suitable locknut must be ordered separately.

### Information, conformities and approvals



Article	Order No.	Color	UV	Connecting thread	Clamping range (LW) mm	Contact diameter mm	EH mm	GL mm	SW 1 / 2 mm	PU pcs.
m-seal EMC M12x1,5 3,0-6,5 1)	84201800	Silver	✓	M12x1,5	3 - 6.5	2 - 5	28	6	14	50
m-seal EMC M16x1,5 5,0-10,0 1)	84201802	Silver	✓	M16x1,5	5 - 10	3.5 - 8	33	6	20	50
m-seal EMC M20x1,5 6,0-12,0 1)	84201804	Silver	✓	M20x1,5	6 - 12	4.5 - 10	32	6	24	50
m-seal EMC M20x1,5 7,5-14,0 1)	84201805	Silver	✓	M20x1,5	7.5 - 14	5.5 - 11.5	40	8	24	50
m-seal EMC M25x1,5 10,0-18,0 1)	84201806	Silver	✓	M25x1,5	10 - 18	7 - 14	43	8	30	25
m-seal EMC M32x1,5 16,0-25,0 1)	84201808	Silver	✓	M32x1,5	16 - 25	12 - 20	53	9	40	10
m-seal EMC M40x1,5 22,0-32,0 1)	84201810	Silver	✓	M40x1,5	22 - 32	18 - 27	60.5	9	50	5
m-seal EMC M50x1,5 30,0-38,0 1)	84201812	Silver	✓	M50x1,5	30 - 38	26 - 34	73	9	58	5
m-seal EMC M63x1,5 34,0-44,0 1)	84201814	Silver	✓	M63x1,5	34 - 44	30 - 40	59	14	64 / 68	5

1) With cURus- approval

1) With cURus- approval



## Type m-seal EMC (EMV)

### Material properties



Fitting: Brass nickel-plated  
Sealing ring: Neoprene (CR) Brass nickel-plated  
Neoprene (CR)

### Thermal properties



Temperature / temperature range  
-40 °C - 100 °C / short term: 150 °C

### Protection class



Protection class  
IP68

### Fire properties



Fire classification  
acc. to UL94: V2 self-extinguishing

### Technical information



Halogen-free

### Conformity



RoHS (EC Directive 2011/65/EU)

### Approvals and operating permits



VDE approval



UL Type 4x



cULus approval



cURus approval



## Type m-seal EMC (EMV)

### Classification

ETIM 9: EC000441  
ECLASS 14: 27140801  
UNSPSC 26.0801: 39131711

### General technical data



00

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.

Recommended torques for  
**murrplastik connectors, corrugated  
conduits and cable fittings**



**holders, lock nuts and reducers**





Recommended torques for  
**murrplastik connectors, corrugated conduits and cable fittings,  
holders, lock nuts and reducers**

**Fastening with lock nut**

<b>Metric thread EN 60423</b>	<b>Connecting thread and lock nut made of polyamide</b>	<b>Connection thread and lock nut made of metal</b>
M12x1.5	2.0 Nm	5.0 Nm
M16x1.5	3.0 Nm	7.0 Nm
M20x1.5	4.0 Nm	8.0 Nm
M25x1.5	5.0 Nm	10.0 Nm
M32x1.5	6.0 Nm	12.0 Nm
M40x1.5	11.0 Nm	16.0 Nm
M50x1.5	15.0 Nm	17.0 Nm
M63x1.5	16.0 Nm	18.0 Nm

<b>Pg thread DIN 40430</b>	<b>Connecting thread and lock nut made of polyamide</b>	<b>Connection thread and lock nut made of metal</b>
Pg 7	2.0 Nm	4.0 Nm
Pg 9	2.5 Nm	4.0 Nm
Pg 11	3.5 Nm	6.0 Nm
Pg 13.5	4.0 Nm	7.0 Nm
Pg 16	4.5 Nm	8.0 Nm
Pg 21	7.5 Nm	10.0 Nm
Pg 29	9.0 Nm	13.0 Nm
Pg 36	14.0 Nm	15.0 Nm
Pg 42	15.0 Nm	16.0 Nm
Pg 48	16.0 Nm	17.0 Nm

**Please note the following information:**

- The specified tightening torques are maximum values and should not be exceeded.
- The values are based on measurements under normal climate conditions (23°C / 50% rel. humidity). During assembly and operation, the prevailing climatic conditions should also be taken into account, as these can affect the properties of the components.
- Please consider the properties of the other components with which the murrplastik elements are connected.
- Locking and sealing elements tightened with a lower torque provide better long-term strength.



## Recommended torques for **Screws and nuts**

### Torques for screws and nuts

Thread size	Torques
M4	2.0 Nm
M5	3.0 Nm
M6	4.0 Nm
M8	10.0 Nm
M10	15.0 Nm

### Product examples from our webshop range



**Series m-pro**



**Series m-fix**



**UHE Holder**

on to the product

[shop.murrplastik.de](http://shop.murrplastik.de)

on to the product

[shop.murrplastik.de](http://shop.murrplastik.de)

on to the product

[shop.murrplastik.de](http://shop.murrplastik.de)

More info at

[shop.murrplastik.de](http://shop.murrplastik.de)

**Murrplastik  
Systemtechnik GmbH**

Dieselstraße 10  
71570 Oppenweiler  
Germany

Phone: +49 7191 4820  
info@murrplastik.de

Managing Directors:  
Jürgen Zeltwanger (CEO)  
Gerd Nothdurft (COO)

HRB 271053 Local court Stuttgart  
VAT ID: DE 144 744 122



MP8902834212

23



0601HS

More info at

[murrplastik.de](http://murrplastik.de)